

# HYPERLIFT

Sectional Door Operators

0.55kW  
1.1kW

## Commercial Door Operators

■ German Engineering, built to last.



LED Display

Operation Button

Power Switch

Control Box



Gear Box

Motor

Emergency Release  
chain hoist

Motor

## Advanced and powerful industrial door operator

- Torque monitoring system for additional safety
- Opening speed up to 1m/s
- Accurate limit setting by encoder
- Automatic closing by timer or passing through the photocell
- Protection class IP65
- Multiple safety inputs for safety-edges, lightcurtains, photocells, radars and loop detectors etc.
- Traffic light function
- Clear text display for easy programming
- Service indicator for setting the number of maximum door-cycles until next service
- Clear text failure messages
- Multiple language display, 6 languages available
- Main switch as standard
- Multiple inputs for pull switches, key switches etc.
- 3 programmable relays outputs

Sectional Door Operators		
Application	Sectional door	
HYPERLIFT-model	HL100-ISD	HL140-ISD
Motor power in KW	0.55	1.1
Torque in Nm	100	140
Speed in RPM	5-45	
Frequency converter	Yes	
Force supervision	Yes	
Diameter hollow shaft in mm	25.44	
Endurance	35 c/h	30 c/h
Emergency release	chain hoist	
Limit setting of door travel	digital encoder	
Force of mechanical brake	/	/
Max door area	≤28m <sup>2</sup>	≤49m <sup>2</sup>

ET TECHNOLOGY (WUXI) CO.,LTD

www.etdoor.com  
sales@etdoor.cn

58# xiqun Rd., meicun industrial zone, 214112, Wuxi, Jiangsu, China